

Serial No. 10/077,787

February 3, 2004

Reply to the Office Action dated November 13, 2003

Page 3 of 11

This listing of claims will replace all prior versions, and listings, of claims in the application:

**LISTING OF CLAIMS:**

Claim 1 (previously presented): An oscillator device comprising:  
an oscillation circuit including an NPN oscillation transistor and a buffer amplifier circuit including a PNP buffer amplifier transistor; wherein  
the NPN oscillation transistor and the PNP buffer amplifier transistor are connected in series to a power supply;  
a collector of the NPN oscillation transistor is connected to a power terminal and is grounded via a capacitor;  
a base of the PNP buffer amplifier transistor is grounded via a capacitor;  
at least one of a resistor and an inductor is connected between a collector of the PNP buffer amplifier transistor and the ground;  
the collector of the PNP buffer amplifier transistor is AC-connected to an output terminal; and  
an emitter of the NPN oscillation transistor and an emitter of the PNP buffer amplifier transistor are directly connected.

Claim 2 (original): The oscillator device according to Claim 1, further comprising at least two resistors connected at at least two positions respectively selected from between the power terminal and a base of the NPN oscillation transistor, between the base of the NPN oscillation transistor and a base of the PNP buffer amplifier transistor, and between the base of the PNP buffer amplifier transistor and a ground, such that individual bias voltages are applied to the base of the NPN oscillation transistor and the base of the PNP buffer amplifier transistor.

Claim 3 (original): The oscillator device according to Claim 1, wherein the

Serial No. 10/077,787

February 3, 2004

Reply to the Office Action dated November 13, 2003

Page 4 of 11

oscillation circuit comprises a crystal oscillator connected between a base of the NPN oscillation transistor and a ground, and a capacitance element connected to the crystal oscillator, and the oscillation frequency varies by changing the value of the capacitance element.

Claim 4 (original): The oscillator device according to Claim 3, wherein the oscillator device is a temperature-compensated crystal oscillator device.

Claim 5 (original): The oscillator device according to Claim 1, wherein the NPN oscillation transistor and the PNP buffer amplifier transistor are integrated in a single package.

Claim 6 (previously presented): An oscillator device comprising:  
an oscillation circuit including a PNP oscillation transistor and a buffer amplifier circuit including an NPN buffer amplifier transistor; wherein  
the PNP oscillation transistor and the NPN buffer amplifier transistor are connected in series to a power supply;  
a collector of the PNP oscillation transistor is connected to a power terminal and is grounded via a capacitor;  
a base of the NPN buffer amplifier transistor is grounded via a capacitor;  
at least one of a resistor and an inductor is connected between a collector of the NPN buffer amplifier transistor and the ground;  
the collector of the NPN buffer amplifier transistor is AC-connected to an output terminal; and  
an emitter of the PNP oscillation transistor and an emitter of the NPN buffer amplifier transistor are directly connected.

Claim 7 (original): The oscillator device according to Claim 6, further comprising

Serial No. 10/077,787

February 3, 2004

Reply to the Office Action dated November 13, 2003

Page 5 of 11

at least two resistors connected at at least two positions respectively selected from between the power terminal and a base of the PNP oscillation transistor, between a base of the PNP oscillation transistor and a base of the NPN buffer amplifier transistor, and between the base of the NPN buffer amplifier transistor and a ground, such that individual bias voltages are applied to the base of the PNP oscillation transistor and the base of the NPN buffer amplifier transistor.

Claim 8 (original): The oscillator device according to Claim 6, wherein the oscillation circuit comprises a crystal oscillator connected between a base of the PNP oscillation transistor and a ground, and a capacitance element connected to the crystal oscillator, and the oscillation frequency varies by changing the value of the capacitance element.

Claim 9 (original): The oscillator device according to Claim 8, wherein the oscillator device is a temperature-compensated crystal oscillator device.

Claim 10 (original): The oscillator device according to Claim 6, wherein the PNP oscillation transistor and the NPN buffer amplifier transistor are integrated in a single package.

Claims 11-16 (canceled).

Claim 17. (original) An electronic apparatus comprising the oscillator device according to Claim 1.

Claim 18. (original) An electronic apparatus comprising the oscillator device according to Claim 6.

Serial No. 10/077,787

February 3, 2004

Reply to the Office Action dated November 13, 2003

Page 6 of 11

Claim 19 (canceled).